



SQ40 Printer



Personalizable

Paper outlet at the front or top



Very compact

only 133x126x130mm, without compromising performance



Performance

Very high printing speed, 300 mm/second



Data buffers

receives new data even during printing.

CONFIGURATION AND TECHNICAL DATA

The new SQ40 from Pulse represents the state of the art in compact printers. It can be positioned either at the front or at the top of the paper outlet for maximum flexibility. It can use the new environmentally friendly thermal paper and its 300mm/second performance puts it at the forefront of high speed printers.



Model	SQ40
Print type	direct thermal printing
Velocity	300mm/s
Width	79.5±0.5mm
Print area	72mm (configurable)
Max. Width	080mm
Paper thickness	0.06-0.08mm
Capacity	576 dots/line - 512 dots/line
Interline	3.75mm (configurable)
Commands	Compatible with ESC/POS
Interfaces	USB, Serial, Ethernet
Character size	ANK, Fant A 12-24 dots - Fant B 9-17 dots
Dimensions	133-126-130mm (D·W·H)
Weight	1.115 KG
Barcode	UPC-A / UPC-E / JA(EAN13) / JAN8(EAN8) / CODE39 / ITF / CODABAR / CODE 93 CODE128
2D Codes	QRCODE / PDF417
Code page	PC347(Europe Standard), PC850(Multi language)
Cut	Partial
Cutter	up to 1.5 million cuts
Printhead	Lifespan up a 100Km
Input Buffer	2048 Kbyte
NV flash	256 Kbyte
Input voltage	DC 24V/2.5A
Voltage port drawer	DC 24V/1A
Working temperature	Temp.: 0-45, 10-80RHo/
Storage temperature	Temp.: 0-60, 10-90RHo/
Supported operating systems	Win XP / Win Vista / Win 7 / Win 8 / Win 8.1 / Win 10 / Linu
Warranty Care 2 years	

SIMPLE ROLL CHANGE



INTERFACES

